





Key Feature

- IP video intercom kit for villa or house, only one call button;
- DS-KV6113-WPE1 x1;
- DS-KH6320-WTE1 x1;
- PSU x2;

Specification

Door station		
Operation system	Embedded Linux operation system	
Flash	32 MB	
RAM	256 MB	
Door station		
Camera	2MP HD camera	
Night vision	Low illumination IR supplement mode:3 m	
Backlight compensation	Support	
Digital noise reduction	Support	
WDR	True WDR	
Field of view	Horizontal: 129° Vertical: 75°	
Video Compression Standard	H.264	
Stream	Main stream: 1080p@30fps, 720p@25fps Sub stream: D1@25fps	
Motion detection	Support	

Flash-avoid	50 Hz, 60 Hz	
frequency	30 Hz, 60 Hz	
Door station		
Audio input	Built-in omnidirectional microphone	
Audio output	Built-in loudspeaker	
Audio quality	Noise suppression and echo cancellation	
Audio		
compression	G.711 U	
standard		
Audio		
compression	64 Kbps	
Rate		
Audio intercom	Two-way audio communication	
Door station		
Network	Top/ID DCTD	
protocol	TCP/IP, RSTP	
Wired network	10/100 Mbps Ethernet	
Door station		
RS-485	1	
Alarm input	4	
Debugging port	1	
Grounding	1	
TAMPER switch	1	
Door station		
Power	< 10 W	
consumption	< 10 W	
Working	40° C+0 E2° C/40° E+0 127.4° E\	
temperature	-40° C to 53° C(-40° F to 127.4° F)	
Working	10% to 95%	
humidity		



Dimension	138 mm $ imes$ 65 mm $ imes$ 27 mm
Installation	Surface mounting
Protection level	IP65
Indicator	2
	IEEE802.3af, standard PoE
Power supply	12 VDC
Indoor station	
Operation	Embodded Linux appration system
system	Embedded Linux operation system
Memory	128 MB
Flash	32 MB
Indoor station	
Display screen	7-inch colorful TFT screen
Display	1024 × 600
resolution	1024 × 600
Operation	Constitue to sale and a
method	Capacitive touch screen
Indoor station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio quality	Noise suppression and echo cancellation
Audio	
compression	G.711 U
standard	
Audio	
compression	64 Kbps
Rate	
Indoor station	
Wired network	10/100 Mbps self-adaptive
Wireless	Wi-Fi 802.11 b/g/n
network	W111002.11 5/6/11
Protocol	TCP/IP, SIP, RTSP
RS-485	1 RJ-45 10/100 Mbps self-adaptive
Indoor station	
RS-485	1
Alarm input	8-ch alarm inputs
Relay output	2
TF card	Max to 32 G, SD 2.0 or lower version
Indoor station	
Power	≤ 6 W
consumption	۷۷ ک
Working	-10 ° C to 55 ° C (14 ° F to 131 ° F)
tomporaturo	
temperature	
Working	10% to 90%

Dimension (L x	200 mm $ imes$ 140 mm $ imes$ 15.1 mm (7.9"
W x H)	× 5.5" × 0.6")

Available Model

DS-KIS603-P(B)(海外标配),DS-KIS603-P(B)(海外中性),

Accessory

Include

DS-KABV6113-RS Villa Door Station Rain Shield







Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T+86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T+99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2020 | Data subject to change without notice |